

Optix MPO 1200 Direct - Indirect
OPTIX SURFACE 1200 MPO D/I HO 4000K DALI EM
2021663



PRODUCT OVERVIEW

Product name	OPTIX SURFACE 1200 MPO D/I HO 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Warranty	5 years
Fixture luminous flux (lm)	5770
Luminaire efficacy (lm/W)	122
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 18
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	47
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216635

DATA TABLE

General data	
Product name	OPTIX SURFACE 1200 MPO D/I HO 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended

Optix MPO 1200 Direct - Indirect

OPTIX SURFACE 1200 MPO D/I HO 4000K DALI EM

2021663

Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	5770
Luminaire efficacy (lm/W)	122
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 18
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Emergency duration (h)	3

Electrical data

Total power consumption (W)	47
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

Lifetime data

Lifespan L70 B50	238000
Lifespan L80 B20	130000
Lifespan L90 B10	58000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	1200
Nominal Product Width (mm)	200
Weight (kg)	4.8

Packaging





Single packaging type	Carton
-----------------------	--------

Optix MPO 1200 Direct - Indirect

OPTIX SURFACE 1200 MPO D/I HO 4000K DALI EM 2021663

Product EAN number	5025768216635
Packaging single width (cm)	22.5
Packaging single depth (cm)	6.8
DUN14 (outer)	05025768216635
Packaging outer length / height (cm)	122.0

PHOTOMETRY



TECHNICAL DRAWINGS

