

Data Sheet | Item Number: 706-3000/200-200

System cable; for Schneider Modicon Edge I/O NTS; 8 digital outputs; Length: 2 m; Conductor cross-section: 0.14 mm²

<https://www.wago.com/706-3000/200-200>



Color coding acc. to DIN VDE 47100		10 poles flat connector		Connector NTSXTB12200H	
		Pin number	Wiring	Pin number	Signal
White		1	0.0 / REL.1	1	DO0
Brown		2	0.1 / REL.2	2	DO1
Green		3	0.2 / REL.3	3	DO2
Yellow		4	0.3 / REL.4	4	DO3
Grey		5	0.4 / REL.5	7	DO4
Pink		6	0.5 / REL.6	8	DO5
Blue		7	0.6 / REL.7	9	DO6
Red		8	0.7 / REL.8	10	DO7
Black		9	+	5-11	24Vin
Violet		10	-	6-12	0Vin

Notes

Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.
------	---

Electrical data

Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	Pluggable connector per DIN 41651; female connector
Pole number 1	10
Connection type	System
Wire cross-section	0.14 mm ²

Connection 2

Connector	Schneider NTSXTB12200H
Pole number	12
Connection type	System
Wire cross-section	0.14 mm ²

Connection 3

Connection type	System
Wire cross-section	0.14 mm ²



Physical data		
Cable length		2 m

Material data		
Weight		130 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +50 °C

Commercial data		
PU (SPU)		1 pcs
Packaging type		Bag
Country of origin		FR
GTIN		4066966891157
Customs tariff number		85444290900

Product Classification		
ETIM 10.0		EC000237
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption