

Data Sheet | Item Number: 706-3000/201-200
System cable; 8 digital outputs, var. 1; Length: 2 m; Conductor cross-section:
0.14 mm²

<https://www.wago.com/706-3000/201-200>



Color coding acc. to DIN VDE 47100		10 poles flat connector		Connector NTSXTB18200XH	
		Pin number	Wiring	Pin number	Signal
White		1	0.0 / REL.1	1	DO0
Brown		2	0.1 / REL.2	3	DO1
Green		3	0.2 / REL.3	5	DO2
Yellow		4	0.3 / REL.4	7	DO3
Grey		5	0.4 / REL.5	9	DO4
Pink		6	0.5 / REL.6	11	DO5
Blue		7	0.6 / REL.7	13	DO6
Red		8	0.7 / REL.8	15	DO7
Black		9	NC	NC	NC
Violet		10	-	16	OVout

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data	
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A

Connection Data	
Cable type	LiYY
Color code	per DIN VDE 47100
Connection 1	
Pluggable connector	Pluggable connector per DIN 41651; fe- male connector
Pole number 1	10
Connection type	System
Wire cross-section	0.14 mm²

Connection 2	
Connector	Schneider NTSXTB18200XH
Pole number	18
Connection type	System
Wire cross-section	0.14 mm²

Connection 3	
Connection type	System
Wire cross-section	0.14 mm²



Physical data	
Cable length	2 m

Material data	
Fire load	0 MJ
Weight	127 g

Environmental requirements	
Ambient temperature (operation)	-20 ... +50 °C

Commercial data	
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4066966891164
Customs tariff number	85444290900

Product Classification	
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption