

Data Sheet | Item Number: 706-3000/401-200

System cable; 6 analog inputs; Length: 2 m; Conductor cross-section: 0.25 mm²

<https://www.wago.com/706-3000/401-200>



Color coding acc. to DIN VDE 47100		Sub-D 25 poles connector		Connector NTSXTB18-200H	
		Pin number	Wiring	Pin number	Wiring
White		1	0+	1	A10/EXC0+
Brown		2	0-	3	EXC0-
Green		3	1+	4	A11/EXC1+
Yellow		4	1-	6	EXC1-
Grey		5	2+	7	A12/EXC2+
Pink		6	2-	9	EXC2-
Blue		7	3+	10	A13/EXC3+
Red		8	3-	12	EXC3-
Black		9	4+	13	A14/EXC4+
Violet		10	4-	15	EXC4-
Grey-Pink		11	5+	16	A15/EXC5+
Red-Blue		12	5-	18	EXC5-
White-Green		13	NC	NC	NC
Brown-Green		14	NC	NC	NC
White-Yellow		15	NC	NC	NC
Yellow-Brown		16	NC	NC	NC
Shield		Connected to Sub-D			

Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Electrical data

Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Connection Data

Cable type	LiYCY
Color code	per DIN VDE 47100

Connection 1

Pluggable connector	D-sub female connector
Pole number 1	25
Connection type	System
Wire cross-section	0.25 mm ²

Connection 2

Connector	Schneider NTSXTB18200H
Pole number	18
Connection type	System
Wire cross-section	0.25 mm ²

Connection 3

Connection type	System
Wire cross-section	0.25 mm ²



Physical data	
Cable length	2 m

Material data	
Weight	278 g

Environmental requirements	
Ambient temperature (operation)	-20 ... +50 °C

Commercial data	
PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4066966891058
Customs tariff number	85444290900

Product Classification	
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption