

Conductor cross-section: 0.25 mm²



Color coding acc. to DIN VDE 47100		Sub-D 25 poles connector		Connector NTSXTB1200XH	
		Pin number	Wiring	Pin number	Wiring
White		1	0+	2	A0+
Brown		2	0-	17	COM
Green		3	1+	4	A1+
Yellow		4	1-	17	COM
Grey		5	2+	6	A12+
Pink		6	2-	17	COM
Blue		7	3+	8	A13+
Red		8	3-	17	COM
Black		9	4+	10	A14+
Violet		10	4-	18	COM
Grey-Pink		11	5+	12	A15+
Red-Blue		12	5-	18	COM
White-Green		13	6+	14	A16+
Brown-Green		14	6-	18	COM
White-Yellow		15	7+	16	A17+
Yellow-Brown		16	7-	18	COM
Shield		Connected to Sub-D			

Note When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	2 A

Cable type	LiYCY
Color code	per DIN VDE 47100

Pluggable connector	D-sub female connector
Pole number 1	25
Connection type	System
Wire cross-section	0.25 mm ²

Connector	Schneider NTSXTB18200XH
Pole number	18
Connection type	System
Wire cross-section	0.25 mm ²

Connection type	System
Wire cross-section	0.25 mm ²



Physical data		
Cable length		2 m

Material data		
Weight		392 g

Environmental requirements		
Ambient temperature (operation)		-20 ... +50 °C

Commercial data		
PU (SPU)		1 pcs
Packaging type		Bag
Country of origin		FR
GTIN		4066966890891
Customs tariff number		85444290900

Product Classification		
ETIM 10.0		EC000237
ECCN		NO US CLASSIFICATION

Environmental Product Compliance		
RoHS Compliance Status		Compliant, No Exemption