


Concord

OFFICELYTE 600 4000K HO SSA03
2069510



Features

• Concord OFFICELYTE 600 4000K HO SSA03 is a high performance low glare luminaire for offices and education applications. Suitable for lay in, as well as for pull up, into concealed grid and plasterboard ceilings with our optional wedge accessory kits suitable. Optical solution is a combination of Tp(a) rated central prismatic and side diffusers. Painted steel housing with RAL 9016 finishing colour. 595x595x92mm dimensions. 4400lm luminous flux, 34.5W total power consumption, 128lm/W efficacy level, CRI80 4000K (Neutral white) LED light sources with chromaticity tolerance of 3-step MacAdam ellipse. Conforming to EN 12464-1 for indoor work places, UGR<19. IK03 impact resistance, IP20 ingress protection level. IEC Class II electrical protection. Photobiological Risk Group 1. Lifespan 93k hours at L80B50. Glow Wire test 650°C. SylSmart Connected enabled with integrated sensor.

Product Overview


Product name	OFFICELYTE 600 4000K HO SSA03
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Office, Education
ETIM Class	EC002892
Fixture luminous flux (lm)	4,400
Luminaire efficacy (lm/W)	128
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80

Concord

OFFICELYTE 600 4000K HO SSA03 2069510

Colour Variation Initial (SDCM)	3
Beam Angle (°)	87
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	34.5
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	RAL9016
IP rating	IP20
IK rating	IK03
Product EAN number	5025768695102
Warranty	5 years
Dimming method	SylSmart SSA

Photometry



Technical drawings

