

Data Sheet | Item Number: 706-3340/5302-100
System cable; for Schneider Modicon M340; 4 x 8 digital inputs or outputs; Length:
1 m; Conductor cross-section: 0.14 mm²; 857 Series
<https://www.wago.com/706-3340/5302-100>



Similar to illustration



Similar to illustration

Data sheet for WAGO 706-3340/5302-100 Data sheet 10		WAGO terminal block		WAGO terminal block		WAGO terminal block	
		Pin	Wire	Pin	Wire	Pin	Wire
WAGO		1	10	10	10	10	10
WAGO		2	10	10	10	10	10
WAGO		3	10	10	10	10	10
WAGO		4	10	10	10	10	10
WAGO		5	10	10	10	10	10
WAGO		6	10	10	10	10	10
WAGO		7	10	10	10	10	10
WAGO		8	10	10	10	10	10
WAGO		9	10	10	10	10	10
WAGO		10	10	10	10	10	10
WAGO		11	10	10	10	10	10
WAGO		12	10	10	10	10	10
WAGO		13	10	10	10	10	10
WAGO		14	10	10	10	10	10
WAGO		15	10	10	10	10	10
WAGO		16	10	10	10	10	10
WAGO		17	10	10	10	10	10
WAGO		18	10	10	10	10	10
WAGO		19	10	10	10	10	10
WAGO		20	10	10	10	10	10
WAGO		21	10	10	10	10	10
WAGO		22	10	10	10	10	10
WAGO		23	10	10	10	10	10
WAGO		24	10	10	10	10	10
WAGO		25	10	10	10	10	10
WAGO		26	10	10	10	10	10
WAGO		27	10	10	10	10	10
WAGO		28	10	10	10	10	10
WAGO		29	10	10	10	10	10
WAGO		30	10	10	10	10	10
WAGO		31	10	10	10	10	10
WAGO		32	10	10	10	10	10

Notes	
Note	When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Electrical data	
Inputs/outputs	4 x 8 digital inputs or outputs
Operating voltage	≤ 35 VAC/VDC
Current per wire (max.)	1 A



Connection Data

Cable type	LiYY
Color code	per DIN VDE 47100

Connection 1	
Pluggable connector	Pluggable connector per DIN 41651; fe- male connector
Pole number 1	14
Connection type	System
Wire cross-section	0.14 mm²

Connection 2	
Connector	Pluggable connector per DIN 41651; fe- male connector
Pole number	14
Connection type	System
Wire cross-section	0.14 mm²

Connection 3	
Connector	Pluggable connector per DIN 41651; fe- male connector
Pole number	14
Connection type	System

Connection 4	
Connector	Pluggable connector per DIN 41651; fe- male connector
Pole number	14
Connection type	System

Connection 5	
Connector 5	Fujitsu FCN-367-J40/AU/H
Pole number	40
Connection type	System

Physical data

Cable length	1 m
--------------	-----

Material data

Fire load	0 MJ
Weight	190 g

Environmental requirements

Ambient temperature (operation)	-20 ... +50 °C
---------------------------------	----------------

Commercial data

PU (SPU)	1 pcs
Packaging type	Bag
Country of origin	FR
GTIN	4066966869194
Customs tariff number	85444290900

Product Classification

UNSPSC	26121629
ETIM 10.0	EC000237
ECCN	NO US CLASSIFICATION



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 706-3340/5302-100	