



Features

- OPTIX SURFACE 1200 MPO D HO 4000K DALI EM is a high efficacy low glare surface or suspended LED Linear luminaire with Micro Prismatic diffuser, with direct light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI Dimmable, 3hr maintained emergency version, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3550lm luminous flux, 33W power consumption, 107lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 3000 cd/m2, lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.


Product Overview

Product name	OPTIX SURFACE 1200 MPO D HO 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	107
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 20
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	33
Electrical protection	Class I


OPTIX SURFACE 1200 MPO D HO 4000K DALI EM
2021667

Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216673
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX SURFACE 1200 MPO D HO 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	107
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 20
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Emergency duration (h)	3

ELECTRICAL DATA

Total power consumption (W)	33
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

LIFETIME DATA

Lifespan L70 B50	238000
Lifespan L80 B20	130000
Lifespan L90 B10	58000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser material	PMMA Acrylic
Nominal Product Length (mm)	1200
Nominal Product Width (mm)	200
Weight (kg)	4.7

PACKAGING

Concord

OPTIX SURFACE 1200 MPO D HO 4000K DALI EM 2021667

Single packaging type	Carton
Product EAN number	5025768216673
Packaging single width (cm)	22.5
Packaging single depth (cm)	6.8
DUN14 (outer)	05025768216673
Packaging outer length / height (cm)	122.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No