

UFH-0605MDSS11: 11-groups Manif. ss ,adjust.+flow met.+thermo,fill+dr. val., arv 11way



Commercial information

- Adjustable flowmeters Adaptable brackets in composite
- Integrated air vent, drain and filling tap
- 1" connection with union nut
- Integrated control valves
- Compact design

Certificates

Applications

Heating, Cooling, Underfloor Heating

Solutions

Underfloor heating, Building installations, Industry, Utility



Technical characteristics

Connection type primary side	2-pipe	Outer pipe diameter primary connection	32 Millimetre
Suitable for cooling	✓	Medium temperature (continuous)	5 55 Degrees celsius
Material	Stainless steel	Max. operating pressure	6 Bar
Position primary connection	Left/right	Max. number of expansion groups	0
Primary connection	Internal thread cylindrical BSPP-G (ISO 228-1)	Number of groups secondary	11
Nominal diameter primary connection	1 inch (25)	Outer pipe diameter secondary	12 20 Millimetre
With valves on primary connection	×	Flow-through capacity	0 5 Litre per hour
With mixing valve	×	Min. pressure difference secondary flow/return	0 Kilo Pascal
Expandable	×	Width	120 Millimetre
Multi-zone manifold	×	Height	190 Millimetre
With temperature limit	×	Depth	770 Millimetre
With non-return valve	×		
With circulation pump	×		
Article compression class	PN 6		
With controller	×		
Hydraulic balance control	None		
Volume flow measurement	Analogue		
With thermometer	×		
Temperature measurement supply	None		
Temperature measurement return	None		
With de-aeration	✓		
With pressure gauge	×		
Secondary connection	Euroconus standardless		
Nominal diameter secondary connection	3/4 inch (20)		
Closable groups	✓		
With flow-through indicator	✓		
With thermal actuator	×		
With wall-mounting bracket	✓		
With casing	×		

Related products

Product code	GTIN	Description	Image
UFH-CAB-O1015Z	05414764400610	Henco Surface mount cabinet backless RAL9003 internal width 1015MM	
UFH-CAB-O1015	05414764400610	Henco Surface mount cabinet RAL9003 internal width 1015MM	
UFH-CAB-I965	05414764400610	Henco Recessed manifold cabinet RAL9003 internal width 965MM	

