

Concord

ROUTELED II OPEN AREA 2059459



Features

- Miniature emergency recessed luminaire downlight with open area optic, non-maintained 3 hr emergency, standalone unit with inverter module and rechargeable battery (NiMH), quick and easy installation with inverter module and battery pack contained in articulated case that can pass through 40mm cutout, 219lm, 3W, IK07, beam angle 148 degrees, 230V, 50-60Hz, recharge period 24 hours, Power Factor 0.45, charge current 300mA, LxWxD (mm) 416x29x26.


Product Overview

Product name	ROUTELED II OPEN AREA
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Fixture luminous flux (lm)	219
LOR (%)	100
Colour temperature (K)	5000
Light colour	Cool White
CRI (Ra)	70
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	5
Photobiological Risk Group	RG0
Luminous flux (emergency) (lm)	219
Electrical protection	Class II
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768594597
Warranty	5 years

Concord

ROUTELED II OPEN AREA 2059459

Photometry



Technical drawings

