

Concord

OPTIX SURFACE 1200 MPO D/I 4000K EM

2021669



Features

- OPTIX SURFACE 1200 MPO D/I 4000K EM is a high efficacy low glare suspended LED Linear luminaire with Micro Prismatic diffuser, with direct/indirect light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, Constant current driver, 3hr maintained emergency version, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 4900lm luminous flux, 60/40 D/I light distribution ratio, 39W power consumption, 125lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 3000 cd/m², lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.

Product Overview

Product name	OPTIX SURFACE 1200 MPO D/I 4000K EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Suspended
Fixture luminous flux (lm)	4900
Luminaire efficacy (lm/W)	125
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 18
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	39
Electrical protection	Class I

Concord
by SYLVANIA


Concord

OPTIX SURFACE 1200 MPO D/I 4000K EM

2021669

Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216697
Warranty	5 years

Photometry



Technical drawings

