




## UFH-ANC-05: Valve 2x3/4 -M30x1,5-KV 2



### Commercial information

#### Certificates

#### Applications

Heating, Cooling, Underfloor Heating

#### Solutions

Underfloor heating, Building installations, Industry, Utility

## Technical characteristics

Housing material	Brass	Max. pressure difference at 20 °C	0.6 Bar
Connection 1	External thread cylindrical BSPP-G (ISO 228-1)	Medium temperature (continuous)	4 95 Degrees celsius
Connection 2	External thread cylindrical BSPP-G (ISO 228-1)		
Surface protection	Untreated		
Internally lined	Other		
Freeflow	✓		
Self-closing	✗		
Spring closing (NC)	✗		
Spring opening (NO)	✓		
Spindle and/or hand wheel rising	✓		
Connection operation	Other		
Type of shut off valve	Control flap		
Valve controls	Other		
Type of bonnet	Screwed		
Right-angled model	✗		
Bellows seal	✗		
With position indicator	✗		
With drain valve	✗		
Standard construction length	DIN		
With backflow safeguard	✗		
Suitable for liquids	✓		
Suitable for gases	✗		
Suitable for steam	✗		
Stainless steel seat ring	✗		
Spindle seal replaceable under pressure	✗		
Spindle thread not in contact with the medium	✗		
VdS quality mark	✗		
KIWA certified	✗		
Gastec QA mark	✗		
Type approval according to BBR/EKS	✗		

## Related products

Product code	GTIN	Description	Image
CU-ACT-24V	05414764140493	Henco Act With Cable 1M, 24V	
CU-ACT-230V-PLUG	05414764140493	Henco Act For Plugcable, 230V	
CU-ACT-24V-PLUG	05414764140493	Henco Act For Plugcable, 24V	

Image

