


SPIROTECH SPECIFICATION SHEET MultiControlModular M0.3-16.0		SPIROTECH 
Customer:	Project:	Type: EMCM-M0.3-16.0
Reference:		



Design criteria

Medium:	Water / glycol (max 40%)
Min. Pressure:	8.0 bar-g
Discharge:	16.0 bar-g
Max. pressure:	25.0 bar-g
Max. temperature:	70 °C
Ambient temperature:	0 - 40 °C
Refill fluid:	0 - 70 °C

Testing and quality assurance

Running test:	yes
Test medium:	Water
High voltage test:	yes
Test certificate:	no
CE-marking:	yes
Material certificates:	no

Construction materials

Fittings / pipes:	Copper/Brass
Pump:	AISI316
Main pump:	Vertical multistage 2 x 100%
Overflow valve(s)	1 x 100%
Casing:	Galvanised steel plate
Color:	Yellow (RAL 1003)

Power supply

Voltage:	[3x] 400V~/50Hz
Power consumption:	2.4 kW
Protection level:	IPX4D

Dimensions

Height:	1370 mm
Width:	980 mm
Depth:	888 mm
A	482 mm
AA	1052 mm
B	980 mm
C	482 mm
CC	213 mm
EE	558 mm
H	1370 mm
M	1190 mm
MM	728 mm
T	888 mm

Dry weight (approx):	170 kg
----------------------	--------

Connections

1. Refill	Rp1/2
5. suction pipe	R5/4
6. overflow pipe	R1
8. Exp. pressure pipe	Rp6/4