
## Data Sheet | Item Number: 222-415/995-005

Splicing connector with levers; for all conductor types; max. 4 mm<sup>2</sup>; 5-conductor; gray housing; Surrounding air temperature: max 40°C; 2,50 mm²; gray



https://www.wago.com/222-415/995-005





Dimensions in mm

N١	n	t	е	•
v	v	L	C	J

Safety management note

#### NOTICE: Observe installation and safety instructions!

- · Only to be used by electricians!
- Do not work under voltage/load!
- Use only for proper use!
- Observe national regulations/standards/guidelines!
- Observe technical specifications for the products!
- Observe the number of permissible potentials!
- Do not use damaged/dirty components!
- Observe conductor types, cross-sections and strip lengths!
- Insert conductor until it hits the product's backstop!
- Use original accessories!

#### To be sold only with installation instructions!

Safety Information

in grounded power lines

### Electrical data

Ratings per IEC/EN	
Ratings per	EN 60664
Nominal voltage (II/2)	400 V
Rated surge voltage (II/2)	4 kV
Rated current	32 A
Legend (ratings)	(II / 2) ≙ Overvoltage category II / Pollution degree 2

necti	

3	5		Connection 1	
otal number of potentials 1	Connection technology	CAGE CLAMP®		
	Actuation type	Lever		
	Connectable conductor materials	Copper Aluminum		
	Solid conductor	0.08 2.5 mm² / 28 12 AWG		
	Stranded conductor	0.08 2.5 mm² / 28 12 AWG		
	Fine-stranded conductor	0.08 4 mm² / 28 12 AWG		
	Strip length	9 10 mm / 0.35 0.39 inches		

# Data Sheet | Item Number: 222-415/995-005

https://www.wago.com/222-415/995-005



### Connection 1

Wiring direction Side-entry wiring

Physical data	
Width	26.6 mm / 1.047 inches
Height	14.5 mm / 0.571 inches
Depth	20.5 mm / 0.807 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Flammability class per UL94	VO
Fire load	0.141 MJ
Actuator color	orange
Weight	6.6 g

Environmental requirements		
Ambient temperature (operation)	+40 °C	
Continuous operating temperature	85 °C	

Commercial data	
PU (SPU)	90 (5) pcs
Packaging type	Blister foil
Country of origin	DE
GTIN	4066966001587
Customs tariff number	85369010000

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

### Downloads

# **Environmental Product Compliance**

#### Compliance Search

Environmental Product Compliance 222-415/995-005



# Data Sheet | Item Number: 222-415/995-005

https://www.wago.com/222-415/995-005



- 1 Compatible Products
- 1.1 Optional Accessories
- 1.1.1 Mounting adapter
- 1.1.1.1 Mounting accessories



Item No.: 222-500

Mounting carrier; 222 Series; for DIN-35 rail mounting/screw mounting; orange

Subject to changes. Please also observe the further product documentation!