

## 8HNA-PK75: Henco Press 75x75



### Commercial information

The Henco Super Size range refers to the Henco multilayer pipe and the Henco fittings in diameters 75 - 90 - 110 mm, with reducing couplings for diameters 32 - 40 - 50 - 63 mm. The fittings assure a complete multilayer piping system with multiple variations for distribution and riser systems. The numerous combinations and the revolutionary connection technique make this system extremely flexible. The Henco Super Size fittings are made of the Polyvinylidene Fluoride (PVDF), a high quality synthetic material. The PVDF offers the user a unique combination of properties:

- corrosion resistant
- excellent mechanical strength and hardness
- resistant to extreme temperatures: from -40°C to +150°C
- approved for contact with water and food
- a maximum working pressure up till 10 bar and a maximum working temperature up till 95°C

All these favourable properties make this multilayer system suitable for numerous applications such as drinking water installations, heating installations and installations in the chemical and food industry. The Henco Super Size fittings are just like all other Henco fittings designed with a leak before press detection.

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 97 mm    |
| Length     | 82 mm    |
| Width      | 82 mm    |
| Net weight | 0.381 kg |

#### Certificates

KIWA, KOMO, DVGW Wasser, ATG, WRAS, STF, ETA, SINTEF, RISE

#### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

|                                 |                                                |                                  |                        |
|---------------------------------|------------------------------------------------|----------------------------------|------------------------|
| Material                        | Plastic                                        | Bend radius                      | 0 Millimetre           |
| Material connection 1           | Polyvinylidene fluoride (PVDF)                 | Outer pipe diameter connection 1 | 75 Millimetre          |
| Material quality                | Polyvinylidene fluoride (PVDF)                 | Outer pipe diameter connection 2 | 75 Millimetre          |
| Material quality connection 1   | Polyvinylidene fluoride (PVDF) (expired)       | Zeta value                       | 0.409                  |
| Surface protection connection 1 | Untreated                                      | Length                           | 82 Millimetre          |
| Surface treatment connection 1  | Untreated                                      | Length of connection 1           | 97.5 Millimetre        |
| Material connection 2           | Polyvinylidene fluoride (PVDF)                 | Working length connection 1      | 27.5 Millimetre        |
| Material quality connection 2   | Polyvinylidene fluoride (PVDF) (expired)       | Wrench width union nut           | 0 Millimetre           |
| Surface protection connection 2 | Untreated                                      | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Surface treatment connection 2  | Untreated                                      | Max. operating pressure at 20 °C | 10 Bar                 |
| Shape                           | Straight                                       | Standard Dimension Ratio (SDR)   | 0                      |
| Reducing                        | ✗                                              |                                  |                        |
| Eccentric                       | ✗                                              |                                  |                        |
| System specific                 | ✓                                              |                                  |                        |
| Connection 1                    | Press sleeve                                   |                                  |                        |
| Connection 2                    | Press sleeve                                   |                                  |                        |
| Main colour fitting             | Black                                          |                                  |                        |
| Material sealing                | Ethylene-propylene diene monomer rubber (EPDM) |                                  |                        |
| With buffer stud                | ✗                                              |                                  |                        |
| Self-sealing                    | ✗                                              |                                  |                        |
| Ring stiffness class            | Other                                          |                                  |                        |
| With sealing rings/gaskets      | ✓                                              |                                  |                        |
| Capped                          | ✗                                              |                                  |                        |
| With drain valve                | ✗                                              |                                  |                        |
| FM quality mark                 | ✗                                              |                                  |                        |
| LPCB quality mark               | ✗                                              |                                  |                        |
| ULC quality mark                | ✗                                              |                                  |                        |
| UL quality mark                 | ✗                                              |                                  |                        |
| VdS quality mark                | ✗                                              |                                  |                        |
| KIWA certified                  | ✓                                              |                                  |                        |
| Gastec QA mark                  | ✗                                              |                                  |                        |