

## Instar Trend 75 Swing IP44 INSTAR TREND SW IP44 INDOOR BA 3079061



### Product features



- INSTAR TREND SW IP44 INDOOR BA





## PRODUCT OVERVIEW

Product name	INSTAR TREND SW IP44 INDOOR BA
Technology	Accessory
Cap/Base	GX5.3
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
General application	Hospitality, Residential & Consumer
ETIM Class	EC001744
E-number FI	4274924
E-number SE	7461924
E-number Norway	3223416
Warranty	3 years
LOR (%)	Dependent on lamp
Light source included	Fixture without Lightsource
Electrical protection	Class III
Control gear mounting	Remote
Housing colour	Aluminium
IP rating	IP44/20
IK rating	IK02
Product EAN number	8711971790617

## PHOTOMETRY




## Instar Trend 75 Swing IP44 INSTAR TREND SW IP44 INDOOR BA 3079061






Distance [m]	Cone diameter [m]	E <sub>0</sub> [lx]	E <sub>0</sub> [fc]
0.5	0.07	4028	4628
1.0	0.15	1004	1154
1.5	0.22	432	492
2.0	0.29	201	231
2.5	0.37	102	117
3.0	0.44	52	60

Distance [m] Cone diameter [m] Illuminance [lx]  
— C0 - C180 (Half beam angle: 8.4°)



Distance [m]	Cone diameter [m]	E <sub>0</sub> [lx]	E <sub>0</sub> [fc]
0.5	0.21	1802	207
1.0	0.42	450	51
1.5	0.64	180	20
2.0	0.86	90	10
2.5	1.07	52	6
3.0	1.29	32	4

Distance [m] Cone diameter [m] Illuminance [lx]  
— C0 - C180 (Half beam angle: 8.4°)



Distance [m]	Cone diameter [m]	E <sub>0</sub> [lx]	E <sub>0</sub> [fc]
0.5	0.08	2046	234
1.0	0.16	511	58
1.5	0.24	205	23
2.0	0.31	102	12
2.5	0.39	61	7
3.0	0.47	38	4

Distance [m] Cone diameter [m] Illuminance [lx]  
— C0 - C180 (Half beam angle: 9.0°)

Distance [m]	Cone diameter [m]	E <sub>0</sub> [lx]	E <sub>0</sub> [fc]
0.5	0.55	264	30
1.0	1.10	66	7
1.5	1.65	29	3
2.0	2.20	15	2
2.5	2.75	9	1
3.0	3.30	5	0.6

Distance [m] Cone diameter [m] Illuminance [lx]  
— C0 - C180 (Half beam angle: 9.0°)

## Instar Trend 75 Swing IP44 INSTAR TREND SW IP44 INDOOR BA 3079061

