


START eco Flood Flat IP65 4500lm 840

Item No: 0047969


SYLVANIA



The new Start eco Flood Flat comes with improved design. The streamlined, durable, lightweight die-cast aluminium body makes it a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black die-cast aluminum housing, white reflector, 4750 lm, 50 W, 95 lm/W, 4000K, drive current 193 mA, non dimmable, CRI>80, IP65, IK07, Class I, lumen maintenance L70:B50: 30000 hrs, 193 x 190 x 48 mm (L x W x H). Weight: 0.785kg. Energy class: A++ A+ A.

Technical Assets

Dimensions (mm)




Photometrics

Distance [m]	Cone diameter [m]	E10' [lx]	E10' [fc]	E10' [fc]
0.5	1.61	670	68.2°	698
1.0	3.23	168	68.2°	125
1.5	4.84	75	68.2°	55
2.0	6.45	45	68.2°	31
2.5	8.06	27	68.2°	20
3.0	9.68	19	68.2°	14

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 116.4°)



START eco Flood Flat IP65 4500lm 840

Item No: 0047969

SYLVANIA

General data

Product name	START eco Flood Flat IP65 4500lm 840
Technology	LED
Housing	Aluminium
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4579437
Warranty	3 years

Optical data

Useful luminous flux (Φuse)	4750
Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	95
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	50
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Electrical protection	Class I
Drive current (mA)	193
Inrush Current (A)	19.8
Inrush Duration (µs)	590
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	13
Max. products per 13A C Breaker	18
Max. products per 16A C Breaker	22
Max. products per 20A C Breaker	27
Max. products per 10A B Breaker	6
Max. products per 13A B Breaker	9
Max. products per 16A B Breaker	11
Max. products per 20A B Breaker	14
Mains surge immunity (differential mode -> L-N) (kV)	1
Mains surge immunity (common mode -> L/N - GND) (kV)	2

Lifetime data

Lifespan L70 B50 | 30000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK07
Nominal Product Length (mm)	193
Nominal Product Width (mm)	190
Nominal Product Height (mm)	48
Weight (kg)	0.785
Wind Area (m ²)	0.036

START eco Flood Flat IP65 4500lm 840

Item No: 0047969

SYLVANIA

Packaging

Product EAN number	5410288479699
Packaging single length / height (cm)	19.5
Packaging single width (cm)	6.0
Packaging single depth (cm)	15.7
DUN14 (inner)	15410288479696
Units per outer package	5
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	21.5
Packaging outer depth (cm)	19.0

Safety data

Optimal operating condition (°C) | -20-40