



## PRODUCT-DETAILS

# S401E-C13NP

## S401E-C13NP Miniature Circuit Breaker

### General Information

Extended Product Type	S401E-C13NP
Product ID	2CCS551103R8134
EAN	7612271442767
Catalog Description	S401E-C13NP Miniature Circuit Breaker
Long Description	Pluggable Miniature circuit-breaker for the SMISLINE TP System acc. IEC/EN 60898-1; IEC/EN 60947-2 Rated short-circuit capacity Icn 6 kA Rated ultimate short-circuit capacity Icu 25 kA Rated current In 13A Tripping characteristic C Poles L + N with protected neutral Rated voltage Ue 230 VAC / 400 VAC

### Ordering

EAN	7612271442767
Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

### Dimensions

Product Net Width	36 mm
Product Net Height	91 mm
Product Net Length	36 mm
Product Net Depth / Length	36 mm
Product Net Weight	288 g

### Container Information

Package Level 1 Units	carton 5 piece
Package Level 1 Width	100 mm
Package Level 1 Height	125 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	1498 g
Package Level 1 EAN	7612271442767

### Environmental

Ambient Air	Operation -25...55 °C
-------------	-----------------------

Temperature

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

**Additional Information**

Ambient Temperature	-25...55 °C
Connecting Capacity	Rigid 0 ... 25 mm <sup>2</sup>
Degree of Protection	IP20
Energy Limiting Class	3
Frequency (f)	50...60 Hz
Input Voltage Type	AC
Number of Poles	2
Number of Protected Poles	2
Object Classification Code	FC
Overvoltage Category	III
Pollution Degree	4
Product Main Type	S400NP
Product Name	Miniature Circuit Breaker
Rated Current (I <sub>N</sub> )	13 A
Rated Frequency (f)	50-60 Hz
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	4 kV
Rated Insulation Voltage (U <sub>i</sub> )	440 V
Rated Operational Voltage	240 V AC
Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )	(230 V AC) 6 kA
Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> )	50 %
Rated Short-Circuit Capacity (I <sub>cn</sub> )	(230 V) 6 kA
Rated Voltage (U <sub>r</sub> )	240 V
Release Type	C
RoHS Date	20170426
Standards	IEC/EN 60898-1
Tripping Characteristic	C

**Certificates and Declarations (Document Number)**

Data Sheet, Technical Information	9AKK107492A6192
Declaration of Conformity - CE	9AKK107991A9633
Environmental Information	2CCC451024D0241
Instructions and Manuals	2CCC451019M0109
RoHS Information	9AKK107991A9633
Dimension Diagram	9AKK107492A6192

**Classifications**

ETIM 4

EC000042 - Miniature circuit breaker (MCB)

ETIM 5	EC000042 - Miniature circuit breaker (MCB)
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code	FC
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs