



PRODUCT-DETAILS

S402M-UCC3

S402M-UCC3 Miniature Circuit Breaker

General Information

Extended Product Type	S402M-UCC3
Product ID	2CCS572001R1034
EAN	7612270109951
Catalog Description	S402M-UCC3 Miniature Circuit Breaker
Long Description	Pluggable Miniature circuit-breaker for the SMISSLINE TP System acc. IEC/EN 60947-2 Rated ultimate short-circuit capacity Icu 25 kA (220 VDC) Rated current In 3A Tripping characteristic UCC Poles 2L Rated voltage Ue 220 VDC / 440 VDC

Ordering

E-Number (Switzerland)	809544107
EAN	7612270109951
Minimum Order Quantity	1 piece
Customs Tariff Number	85363000

Dimensions

Product Net Width	36 mm
Product Net Height	91 mm
Product Net Length	75 mm
Product Net Depth / Length	75 mm
Product Net Weight	285 g

Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	91 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	285 g
Package Level 1 EAN	7612270109951

Environmental

Ambient Air	Operation -25...55 °C
-------------	-----------------------

Temperature

RoHS Status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Ambient Temperature	-25...55 °C
Connecting Capacity	Rigid 0 ... 25 mm ²
Degree of Protection	IP20
Energy Limiting Class	3
Frequency (f)	50 ... 60 Hz
Input Voltage Type	AC/DC
Number of Poles	2
Number of Protected Poles	2
Object Classification Code	FC
Overvoltage Category	III
Pollution Degree	2
Power Loss	1.49 W
Product Main Type	S400
Product Name	Miniature Circuit Breaker
Rated Current (I _N)	3 A
Rated Frequency (f)	50-60 Hz
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Insulation Voltage (U _i)	440 V
Rated Operational Voltage	440 V DC 220 V DC 240 / 415 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(400 V AC) 7.5 kA
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs})	50 %
Rated Short-Circuit Capacity (I _{cn})	(400 V) 10 kA (230 V) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(440 V DC) 25 kA
Rated Voltage (U _r)	440 V DC
Release Type	C
RoHS Date	20170426
Standards	IEC/EN 60947-2
Tripping Characteristic	UC-C

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107492A6192
Declaration of Conformity - CE	9AKK107991A9644
Environmental Information	2CCY000200D0223
Instructions and Manuals	2CCC451019M0109
RoHS Information	2CCC413008D0206_RoHS
Dimension Diagram	9AKK107492A6192

Classifications	
ETIM 4	EC000042 - Miniature circuit breaker (MCB)
ETIM 5	EC000042 - Miniature circuit breaker (MCB)
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code	FC
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs