



Features

- Fixed accent LED downlight, with deepened LED position for low glare and comfortable light. Wide range of tool less replaceable reflectors, complete with leading / trailing edge driver and Loop in Loop out connector, black aluminium heatsink and white front bezel, with sandblasted aluminium reflector, 884LM, 13W, 68lm/W, 3000K Driver current: 250mA, CRI80, 40° beam angle, leading / trailing edge dimmable, IP44, IK02, 35,000 hrs (L70), (WxD) 90x100mm,

Product Overview

Product name	STELLO COMFORT LED FIX WW + DB
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
E-number FI	4271085
E-number SE	7475355
Fixture luminous flux (lm)	884
Luminaire efficacy (lm/W)	68
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Total power consumption (W)	13
Electrical protection	Class II
Control gear type	Electronic ballast
Housing colour	White
IP rating	IP44/20
IK rating	IK02
Product EAN number	8711971793618
Warranty	3 years

STELLO COMFORT LED FIX WW + DB 3079361

Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
Environment	Indoor
E-number FI	4271085
E-number SE	7475355
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	884
Luminaire efficacy (lm/W)	68
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Adjustable chromaticity	N

ELECTRICAL DATA

Total power consumption (W)	13
Electrical protection	Class II
Control gear required	No
Control gear type	Electronic ballast
Drive current (mA)	250
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	F

LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

PHYSICAL DATA

Housing colour	White
IP rating	IP44/20

STELLO COMFORT LED FIX WW + DB 3079361

IK rating	IK02
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Diameter (mm)	90
Weight (kg)	0.509
Recessed Depth (mm)	110

PACKAGING

Single packaging type	Carton
Product EAN number	8711971793618
Packaging single width (cm)	15.7
Packaging single depth (cm)	10.0
DUN14 (outer)	18711971793615
Packaging outer length / height (cm)	49.1

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No