

PRODUCT-DETAILS

S403M-B32

S403M-B32 Miniature Circuit Breaker

General Information

| | |
|-----------------------|--|
| Extended Product Type | S403M-B32 |
| Product ID | 2CCS573001R0325 |
| EAN | 7612270102822 |
| Catalog Description | S403M-B32 Miniature Circuit Breaker |
| Long Description | Pluggable Miniature circuit-breaker for the SMISLINE TP System acc. IEC/EN 60898-1 Rated short-circuit capacity Icn 10 kA Rated current In 32A Tripping characteristic B Poles 3L Rated voltage Ue 230 VAC / 400 VAC |

Ordering

| | |
|------------------------|---------------|
| E-Number (Switzerland) | 809082807 |
| EAN | 7612270102822 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362020 |

Dimensions

| | |
|----------------------------|-------|
| Product Net Width | 54 mm |
| Product Net Height | 91 mm |
| Product Net Length | 82 mm |
| Product Net Depth / Length | 82 mm |
| Product Net Weight | 401 g |

Container Information

| | |
|--------------------------------|----------------|
| Package Level 1 Units | carton 3 piece |
| Package Level 1 Width | 185 mm |
| Package Level 1 Height | 89 mm |
| Package Level 1 Depth / Length | 101 mm |
| Package Level 1 Gross Weight | 1320 g |
| Package Level 1 EAN | 7612270102822 |

Environmental

Ambient Air

Operation -25...55 °C

Temperature

RoHS Status Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

| | |
|---|--------------------------------|
| Ambient Temperature | -25...55 °C |
| Connecting Capacity | Rigid 0 ... 25 mm ² |
| Degree of Protection | IP20 |
| Energy Limiting Class | 3 |
| Frequency (f) | 50 ... 60 Hz |
| Input Voltage Type | AC |
| Number of Poles | 3 |
| Number of Protected Poles | 3 |
| Object Classification Code | FC |
| Overvoltage Category | III |
| Pollution Degree | 3 |
| Power Loss | 8.1 W |
| Product Main Type | S400 |
| Product Name | Miniature Circuit Breaker |
| Rated Current (I _n) | 32 A |
| Rated Frequency (f) | 50-60 Hz |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV |
| Rated Insulation Voltage (U _i) | 440 V |
| Rated Operational Current (I _e) | 32 A |
| Rated Operational Voltage | 240 / 415 V AC |
| Rated Service Short-Circuit Breaking Capacity (I _{cs}) | (400 V AC) 7.5 kA |
| Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{cs}) | 50 % |
| Rated Short-Circuit Capacity (I _{cn}) | (400 V) 10 kA (230 V) 10 kA |
| Rated Voltage (U _r) | 230 / 400 V |
| Release Type | B |
| RoHS Date | 20170426 |
| Standards | IEC/EN 60898-1 |
| Tripping Characteristic | B |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|----------------------|
| Data Sheet, Technical Information | 9AKK107492A6192 |
| Declaration of Conformity - CE | 9AKK107991A9634 |
| Environmental Information | 2CCY451206D0201 |
| Instructions and Manuals | 2CCC451019M0109 |
| RoHS Information | 2CCC413008D0206_RoHS |
| Dimension Diagram | 9AKK107492A6192 |

Classifications

| | |
|----------------------------|--|
| ETIM 4 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 5 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 6 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 7 | EC000042 - Miniature circuit breaker (MCB) |
| Object Classification Code | FC |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers
MCBs