



Features

• OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI is a ceiling recessed LED Linear luminaire with Asymmetric Aluminium Reflector, Asymmetric Light Distribution, Luminaire Dimensions: 1196x293x52mm, Sylvania White body colour, IP20, IK07, DALI dimmable, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3480lm, 30W, 116lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, lifespan: 58,000 hours L90B10.

Product Overview


Product name	OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Fixture luminous flux (lm)	3480
Luminaire efficacy (lm/W)	116
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216864
Warranty	5 years

Concord


OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI

2021686

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting

OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI 2021686

Performance ambient temperature Tq (°C)	25
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3480
Luminaire efficacy (lm/W)	116
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	30
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000

OPTIX RECESSED 1200 ASYMMETRIC 4000K DALI 2021686

Lifespan L90 B10	58000
------------------	-------

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1196
Nominal Product Width (mm)	293
Weight (kg)	5.1

PACKAGING

Single packaging type	Carton
Product EAN number	5025768216864
Packaging single width (cm)	6.5
Packaging single depth (cm)	32.0
DUN14 (outer)	05025768216864
Packaging outer length / height (cm)	124.5

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No