

## 36P-2622P: Press adapter to copper press 26x22 cusi



### Commercial information

- Press-fit adapter (M,V & SA Profile)
- Quick and more reliable solution than compression fittings
- M, V & SA-profile can be used on copper side.
- Can be used in concrete if the fitting is protected
- Can be used in spaces which are difficult to reach
- Brass CW724 "CuSi"
- Compatible with thin-walled steel, copper, stainless steel

### Basic unit dimensions

Height	32 mm
Length	59 mm
Width	32 mm
Net weight	0.113 kg

### Certificates

QB (CSTBat), DVGW Wasser, ÖVGW Wasser, SINTEF, KIWA, KOMO, ATG, ÖN EN 21003-2/-3, ETA, STF, AFNOR, ACS, WRAS, GOST-R, PZH, ITC, TSU, DNV-GL, RISE, EMI

### Applications

Potable water, Heating, Cooling, Compressed air, Sanitary

### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

Material connection 1	Brass	Bend radius	0 Millimetre
Surface protection connection 1	Untreated	Outer pipe diameter connection 1	26 Millimetre
Surface treatment connection 1	Untreated	Outer pipe diameter connection 2	22 Millimetre
Material connection 2	Brass	Wall thickness, connection 2	1.4 Millimetre
Surface protection connection 2	Untreated	Length	59 Millimetre
Surface treatment connection 2	Untreated	Length of connection 1	29 Millimetre
Shape	Straight	Working length connection 1	25 Millimetre
Reducing	✗	Length of connection 2	26.5 Millimetre
Eccentric	✗	Working length connection 2	22.5 Millimetre
System specific	✓	Wrench width	0 Millimetre
Nominal diameter connection 1	DN 25	Wrench width union nut	0 Millimetre
Connection 1	Press sleeve	Medium temperature (continuous)	-10 70 Degrees celsius
Contour code connection 1	TH	Max. operating pressure at 20 °C	16 Bar
Nominal diameter connection 2	DN 20	Standard Dimension Ratio (SDR)	0
Connection 2	Press sleeve		
Main colour fitting	Brass		
Flange compression class (PN)	PN 10		
Material sealing	Ethylene-propylene diene monomer rubber (EPDM)		
With buffer stud	✓		
High tensile strength	✗		
With thermal insulation	✗		
Ring stiffness class	Other		
With sealing rings/gaskets	✓		
Capped	✗		
With drain valve	✗		
With de-aerator	✗		
FM quality mark	✗		
LPCB quality mark	✗		
ULC quality mark	✗		
UL quality mark	✗		
DIN-CERTCO certificate	✗		
VdS quality mark	✗		
With approval for TÜV	✗		
DVGW quality mark for gas	✗		
DVGW quality mark for water	✓		
KIWA certified	✓		
Gastec QA mark	✗		
KOMO certified	✓		
Type approval according to BBR/EKS	✗		