

Optix Recessed 1200 Asymmetric
OPTIX RECESSED 1200 ASYMMETRIC 4000K SSC
2021687



PRODUCT OVERVIEW

Product name	OPTIX RECESSED 1200 ASYMMETRIC 4000K SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Warranty	5 years
Fixture luminous flux (lm)	3480
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG0
Total power consumption (W)	31
Electrical protection	Class I
Control gear type	LED driver constant current
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5025768216871

DATA TABLE

General data	
Product name	OPTIX RECESSED 1200 ASYMMETRIC 4000K SSC
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
Operating temperature range (°C)	10°C...+25°C

Optix Recessed 1200 Asymmetric

OPTIX RECESSED 1200 ASYMMETRIC 4000K SSC

2021687

Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	3480
Luminaire efficacy (lm/W)	112
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	31
Primary Supply/Product voltage - min (V)	198.0
Lamp power factor	0.98
Electrical protection	Class I
Control gear type	LED driver constant current
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 20A B Breaker	27

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000
Lifespan L90 B10	58000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Other
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1196
Nominal Product Width (mm)	293
Weight (kg)	5.2


Packaging

Single packaging type	Carton
Product EAN number	5025768216871
Packaging single width (cm)	6.5

Optix Recessed 1200 Asymmetric
OPTIX RECESSED 1200 ASYMMETRIC 4000K SSC
2021687

Packaging single depth (cm)	32.0
DUN14 (outer)	05025768216871
Packaging outer length / height (cm)	124.5
Safety data	
Optimal operating condition (°C)	10-25

PHOTOMETRY



TECHNICAL DRAWINGS

