

## 1-2606-S: Straight male adapter 26x1



### Commercial information

The body of the Henco fittings is made from brass CuZn40Pb2 (CW617N).

The fittings are provided with O-rings and a union nut. The compression fittings have a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

Henco screw/compression fittings can be used for all applications with a maximum working pressure up to 10 bar, except for pipes which are built in floors or walls.

The body of the Henco screw/compression fittings is manufactured from brass. The fittings are provided with O-rings and a union nut with a clamping ring. Just like the brass press fittings they are fitted with a synthetic buffer ring to prevent electrolysis between the brass and the aluminium.

As in the compression and press fittings range, there are a number of fittings available which allow you to connect copper or steel pipes to Henco pipes.

#### Basic unit dimensions

|            |          |
|------------|----------|
| Height     | 41 mm    |
| Length     | 47 mm    |
| Width      | 41 mm    |
| Net weight | 0.185 kg |

#### Certificates

KIWA, ATG, ETA, ÖVGW Wasser, WRAS, KOMO, ÖN EN 21003-2/-3, GOST-R, ITC, TSU, PZH, Sans 21003, Kontrol Biro, EMI

#### Applications

Potable water, Heating, Cooling, Sanitary

#### Solutions

Building installations, Industry, Utility, Shipbuilding

## Technical characteristics

|                                    |   |                                  |                        |
|------------------------------------|---|----------------------------------|------------------------|
| Material connection 1              | Brass   | Bend radius                      | 0 Millimetre           |
| Material quality connection 1      | CuZn40Pb2 (CW617N)                                    | Outer pipe diameter connection 1 | 26 Millimetre          |
| Surface protection connection 1    | Untreated   | Length                           | 47 Millimetre          |
| Surface treatment connection 1     | Untreated   | Wrench width                     | 0 Millimetre           |
| Material connection 2              | Brass   | Wrench width union nut           | 0 Millimetre           |
| Material quality connection 2      | CuZn40Pb2 (CW617N)                                    | Medium temperature (continuous)  | -10 70 Degrees celsius |
| Surface protection connection 2    | Untreated   | Max. operating pressure at 20 °C | 10 Bar                 |
| Surface treatment connection 2     | Untreated   | Standard Dimension Ratio (SDR)   | 0                      |
| Shape                              | Straight  |                                  |                        |
| Reducing                           | ✘   |                                  |                        |
| Eccentric                          | ✘   |                                  |                        |
| System specific                    | ✓   |                                  |                        |
| Connection 1                       | Compression ring                                      |                                  |                        |
| Nominal diameter connection 2      | 1 inch (25)   |                                  |                        |
| Connection 2                       | External thread conical BSPT-R (ISO 7-1 / EN 10226-1) |                                  |                        |
| Main colour fitting                | Brass   |                                  |                        |
| Material sealing                   | Ethylene-propylene diene monomer rubber (EPDM)        |                                  |                        |
| With buffer stud                   | ✓   |                                  |                        |
| High tensile strength              | ✘   |                                  |                        |
| With thermal insulation            | ✘   |                                  |                        |
| Ring stiffness class               | Other   |                                  |                        |
| With sealing rings/gaskets         | ✓   |                                  |                        |
| Capped                             | ✘   |                                  |                        |
| With drain valve                   | ✘   |                                  |                        |
| With de-aerator                    | ✘   |                                  |                        |
| FM quality mark                    | ✘   |                                  |                        |
| LPCB quality mark                  | ✘   |                                  |                        |
| ULC quality mark                   | ✘   |                                  |                        |
| UL quality mark                    | ✘   |                                  |                        |
| DIN-CERTCO certificate             | ✘   |                                  |                        |
| VdS quality mark                   | ✘   |                                  |                        |
| With approval for TÜV              | ✘   |                                  |                        |
| DVGW quality mark for gas          | ✘   |                                  |                        |
| DVGW quality mark for water        | ✘   |                                  |                        |
| KIWA certified                     | ✓   |                                  |                        |
| Gastec QA mark                     | ✘   |                                  |                        |
| KOMO certified                     | ✓   |                                  |                        |
| Type approval according to BBR/EKS | ✘   |                                  |                        |