

Start Spot Scoop

START SPOT SCOOP 4500LM 940 MB WHITE

0060587



Product features

- Recessed Adjustable Accent Downlight, integrated LED, die cast aluminium body, Ø205mm cut-out, CCT 4000K, SDCM<3, CRI90, 4500lm, total power consumption 48W, resulting in 94lm/W.



PRODUCT OVERVIEW

Product name	START SPOT SCOOP 4500LM 940 MB WHITE
Technology	LED
Housing	Aluminium
Environment	Indoor
General application	Retail
ETIM Class	EC001744
E-number FI	4276984
Warranty	5 years
Useful luminous flux (Fuse)	4500
Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	94
Correlated colour temperature (k)	4000
Colour Code	940
Light colour	Neutral White
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	32
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK03
Product EAN number	5410288605876


PHOTOMETRY

Start Spot Scoop *START SPOT SCOOP 4500LM 940 MB WHITE* 0060587

0.5	0.25 0.25	E:07 2398 E:C90 18.2° 1049 E:C0 18.5° 1067
1.0	0.50 0.50	E:07 5900 E:C90 18.2° 2616 E:C0 18.5° 2611
1.5	0.87 0.88	E:07 2622 E:C90 18.2° 1342 E:C0 18.5° 1198
2.0	1.16 1.16	E:07 1478 E:C90 18.2° 854 E:C0 18.5° 851
2.5	1.46 1.46	E:07 944 E:C90 18.2° 618 E:C0 18.5° 618
3.0	1.74 1.73	E:07 688 E:C90 18.2° 501 E:C0 18.5° 503

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 33.5°)
 — C90 - C270 (Half beam angle: 32.4°)



TECHNICAL DRAWINGS

