Specifications

Photo is representative

Eaton BK/SC-15

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 15 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 100 kAIC at 600 Vac, 10 kAIC at 170 Vdc, Bulk, 600 V, 170 Vdc

General specifications

PRODUCT NAME	Eaton Bussmann series SC fuse
CATALOG NUMBER	BK/SC-15
UPC	051712750097
EAN	5027590455008
PRODUCT LENGTH/DEPTH	0.41 in
PRODUCT HEIGHT	1.31 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.1 lb
WARRANTY	Not Applicable
COMPLIANCES	Not Applicable RoHS Compliant
CATALOG NOTES	Bulk
PRODUCT TYPE	Fuse

Powering Business Worldwide

Electrical rating

AMPERAGE RATING	15 A
INTERRUPT RATING	100 kAIC at 600 Vac 10 kAIC at 170 Vdc
RESPONSE TIME	12 sec at 200%
VOLTAGE RATING	600 Vac, 170 Vdc

Physical details

PACKAGING TYPE	Standard Bulk

General information

CLASS	Class G
CONNECTION	Ferrule end x ferrule end
FUSE INDICATOR	Non-indicating
SPECIAL FEATURES	Rejection style

Resources

CATALOGS	BK/SC-15~BK-SC-15~BUSS SC FUSE CLASS G Bussmann series complete full line catalog no. 1007
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - BK/SC-15

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.