

START Downlight Flat Dimmable 226mm Round Surface

START Downlight Flat 226 1750LM 840 DIM SM
0054129



Product features

- START Downlight Flat DIM Surface is an integrated LED surface mounted downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1750Lm; 103Lm/W; 4000K; IP20.




PRODUCT OVERVIEW

Product name	START Downlight Flat 226 1750LM 840 DIM SM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling surface mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278504
Warranty	5 years
Useful luminous flux (Fuse)	1750
Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Correlated colour temperature (k)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	17
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK06
Product EAN number	5410288541297

PHOTOMETRY

START Downlight Flat Dimmable 226mm Round Surface

START Downlight Flat 226 1750LM 840 DIM SM
0054129



Distance [m]	Cone diameter [m]	E0° [lx]	E15° [lx]	E30° [lx]	E45° [lx]	E60° [lx]	E75° [lx]	E90° [lx]
0.5	1.44	267	232	217				
	1.42							
1.0	2.89	67	58	54				
	2.86							
1.5	4.33	29	25	23				
	4.28							
2.0	5.78	18	14	13				
	5.71							
2.5	7.22	10	9	8				
	7.14							
3.0	8.67	7	6	5				
	8.57							

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 110.0°)
— C90 - C270 (Half beam angle: 110.0°)

TECHNICAL DRAWINGS

