

UFH-ISODRY-25: Systemplatte für trockenbau



Kommerzielle Informationen

With this underfloor heating system the pipe is installed in a preformed gypsum fibre board. The system is particularly suited for low construction heights, such as during renovation. It is important to install the gypsum fibre board on a completely flat surface.

Zertifikate

Anwendungen

Heizung, Kühlung, Fußbodenheizung





Lösungen

Fußbodenheizung, Gebäudeinstallation, Industrie, Tiefbau

Technische Eigenschaften

Werkstoff	Polyethylen (PE)	Breite	500 Millimeter
Noppenplatte	✘	Länge	1000 Millimeter
Tackerplatte	✘	Geeignet für Rohrdurchmesser	16 16 Millimeter
Einlegeplatte	✘		
Klettbefestigung	✘		
Mit Folie	✘		
Mit Wärmeleitplatte	✘		
Mit Trittschalldämmung	✘		
Rollbar	✘		
Zusammenklappbar	✓		

Verwandte Produkte

Produktcode	GTIN	Beschreibung	Bild
BE20	05414764142367	Henco Pressbacken (universal) BE/TH-Profil 20x2	
UFH-DRY-GP100/2	05414764142367	Henco wärmeleitblech für trockenbau	
UFH-DRY-B	05414764142367	Henco Kunststoffreiter für diagonalverlegung	
UFH-FOIL-ALU	05414764142367	Henco Polyethylen-schutzfolie,reflektion alu	
UFH-PLUG80	05414764142367	Henco Niederhaltedübel,bohrer ø8mm,schaftlänge 80mm	