

Concord

OPTIX SURFACE 1500 MPO D 4000K DALI EM 2021705



Features

- OPTIX SURFACE 1500 MPO D 4000K DALI EM is a high efficacy low glare surface or suspended LED Linear luminaire with Micro Prismatic diffuser, with direct light distribution, luminaire dimensions: 1500x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI dimmable, 3hr maintained emergency version, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 4350lm luminous flux, 38W power consumption, 114lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 3000 cd/m², lumen maintenance: L90B50 at 71000h, photobiological safety risk group 1. Electrical protection Class I.

Product Overview

Product name	OPTIX SURFACE 1500 MPO D 4000K DALI EM
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
Fixture luminous flux (lm)	4350
Luminaire efficacy (lm/W)	114
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Glare control	< 20
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	80
Total power consumption (W)	38

Concord
by SYLVANIA

Concord

OPTIX SURFACE 1500 MPO D 4000K DALI EM

2021705

Electrical protection

Class I

Control gear type

LED driver constant current

Housing colour

RAL 9016 - Traffic white / Bezel

IP rating

IP20

IK rating

IK07


Product EAN number

5025768217052

Warranty

5 years

Photometry



Technical drawings

