


Walraven Stud Bolt

(K5505)

for threaded connections, hangers and ties,



Features & benefits

- according to DIN 976-1
- material: steel, strength class 4.8
- zinc plated
- thread with 60° angle provides best performance
- M10 and M12 tested for fire safety according to EN 1363-1



Product Number	VVS Number	Norm / Standard	Thread Size	Total Length	Total Height	Total Width
Reference letter			TS	L	H	W
Unit description				mm	mm	mm
6313802	018048205	DIN 976-1	M8	25	8	8
6313805	018048209	DIN 976-1	M8	50	8	8
6313807	018048212	DIN 976-1	M8	70	8	8
6313808	018048016	DIN 976-1	M8	80	8	8
6313809	018048218	DIN 976-1	M8	90	8	8
6313810	018048220	DIN 976-1	M8	100	8	8
6313812	018048122	DIN 976-1	M8	120	8	8
6313815	018048230	DIN 976-1	M8	150	8	8
6313818	018048128	DIN 976-1	M8	180	8	8
6313820	018048240	DIN 976-1	M8	200	8	8
6313830		DIN 976-1	M8	300	8	8
6323002	018048105	DIN 976-1	M10	25	10	10
6323003		DIN 976-1	M10	30	10	10
6323004	018048108	DIN 976-1	M10	40	10	10
6323005	018048115	DIN 976-1	M10	50	10	10
6323007	018048117	DIN 976-1	M10	70	10	10
6323008	018048116	DIN 976-1	M10	80	10	10
6323009	018048119	DIN 976-1	M10	90	10	10
6323010	018048120	DIN 976-1	M10	100	10	10
6323012	018048124	DIN 976-1	M10	120	10	10
6323015	018048130	DIN 976-1	M10	150	10	10
6323016	018048126	DIN 976-1	M10	160	10	10
6323018	018048129	DIN 976-1	M10	180	10	10
6323020	018048140	DIN 976-1	M10	200	10	10
6323024		DIN 976-1	M10	240	10	10
6323030		DIN 976-1	M10	300	10	10