

Technical data sheet

Quick clip, light grey

Item number: 2149030



Flush-mounted clip to accept metric steel armoured pipes and heavy-duty insulating pipes, as well as Quick Pipe electrical installation pipes. Universal fastening options on walls and ceilings, both in indoor and protected outdoor areas. With slot for side alignment during mounting with wood screw or knock-in anchor. Toolless pipe mounting. Can also be arranged with OBO Multi-Quick or proQuick clip. M16–M32 size can be screwed onto M6 thread. Recommended fastening spacing 50–60 cm, for max. extraction values F at a room temperature of 20 °C, see the table.



Polypropylene Eco

Master data

Item number	2149030
Type	2955 M40 ECO
Description 1	Quick clip
Available from	08.03.2026
Manufacturer	OBO
Dimension	M40
Colour	Light grey; RAL 7035
Material	Polypropylene Eco
Smallest sales unit	50
Unit of quantity	Piece
Weight	0.81 kg
Weight unit	kg/100 pc.


Technical data sheet

Quick clip, light grey

Item number: 2149030



Dimensions



Dimension h	7 mm
-------------	------

Technical data

Expandable	yes
Number of cables/pipes	1
Fastening type	Screw hole
Closed	no
Halogen-free	yes
With inlay	no
Quick clip installation	Durchgangsloch, auf M6 Gewinde aufschraubbar
UV-resistant	no