

Data Sheet | Item Number: 870-402

Jumper; 2-way; insulated; light gray

<https://www.wago.com/870-402>



Color: ■ light gray

Electrical data

Ratings per IEC/EN

Rated current 18 A

Ex information

Rated current (Ex e II) 13.5 A

Physical data

Width 9 mm / 0.354 inches
Height 2.5 mm / 0.098 inches
Jumper assignment 1-2

Material data

Note (material data) [Information on material specifications can be found here](#)
Color light gray
Insulation material (main housing) Polyamide (PA66)
Flammability class per UL94 V0
Fire load 0.01 MJ
Weight 0.8 g

Commercial data

Product Group 16 (Rail Mounted Terminal Blocks with CCC)
PU (SPU) 25 (25) pcs
Packaging type Bag
Country of origin DE
GTIN 4066966272529
Customs tariff number 85366990990

Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Downloads

Environmental Product Compliance

Compliance Search	
Environmental Product Compliance 870-402	↓

Documentation

Bid Text			
870-402	19.02.2019	xml 2.51 KB	↓
870-402	04.01.2018	doc 23.50 KB	↓



CAD/CAE-Data

CAD data	
2D/3D Models 870-402	↓

CAE data	
EPLAN Data Portal 870-402	↓
WSCAD Universe 870-402	↓
ZUKEN Portal 870-402	↓

Installation Notes

Commoning



Commoning with push-in type jumper bars:
Two parallel jumper slots are accommodated in one terminal block.

Push jumper bars down firmly until fully inserted. When using multipole bars, push alternately on the right and then left side until installed.
Push-in type jumper bars 1 – 3 – 5 – 7 or 1 – – 4 – – 7 upon request

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com