



## BAP-FFV3207: Inox ball valve with handle, press x female Ø32 x 1 1/4"



### Commercial information

Henco Inox ball valve with handle, press x female Ø32 x 1 1/4"

#### Basic unit dimensions

Height	97 mm
Length	140 mm
Width	55 mm
Net weight	0.540 kg

#### Certificates

KIWA SE, KIWA

#### Applications

Potable water, Heating, Compressed air, Sanitary

#### Solutions

Building installations, Industry, Utility

## Technical characteristics

Housing material	Stainless steel	Outer pipe diameter connection 2	32 Millimetre
Material quality	Stainless steel 316 L (1.4404)	Medium temperature (continuous)	-10 70 Degrees celsius
Surface protection housing	None	Length of connection 1	61 Millimetre
Material ball	Stainless steel	Working length connection 1	30 Millimetre
Surface protection ball	None	Length of connection 2	78.5 Millimetre
Material spindle	Stainless steel	Working length connection 2	36.5 Millimetre
Material primary spindle seal	Other	Handgrip length	12.2 Millimetre
Material secondary spindle seal	Other		
Nominal diameter connection 1	1 1/4 inch (32)		
Connection 1	Internal thread cylindrical BSPP-G (ISO 228-1)		
With coupling connection 1	✘		
Nominal diameter connection 2	DN 20		
Connection 2	Press sleeve		
With coupling connection 2	✘		
Contour code connection 2	TH/BE		
Article compression class	PN 16		
With drain valve	✘		
With drain possibility (connection)	✘		
With filter	✘		
With thermometer	✘		
Model	Straight		
With insulation shell	✘		
FM quality mark	✘		
UL quality mark	✘		
ULC quality mark	✘		
LPCB quality mark	✘		
Fire-safe	✘		
Medically clean	✘		
Grease-free	✘		
Full bore	✓		
VdS quality mark	✘		
DVGW quality mark for gas	✘		
DVGW quality mark for water	✘		
KIWA certified	✓		
Type approval according to BBR/EKS	✘		