



Color: ■ gray

Electrical data

Ratings per IEC/EN	
Nominal voltage (III/3)	400 V
Rated impulse withstand voltage (III / 3)	6 kV
Rated current	24 A

Physical data

Width	24.5 mm / 0.965 inches
Height	6 mm / 0.236 inches
Jumper assignment	1-6

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Fire load	0.017 MJ
Weight	2.3 g

Commercial data

Product Group	17 (TOP JOB Installation Terminal Blocks)
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4044918271028
Customs tariff number	85366990990



Product Classification	
UNSPSC	39121410
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 780-456


↓

Documentation				
Bid Text				
780-456	19.02.2019	xml	2.91 KB	↓
780-456	28.04.2017	doc	24.00 KB	↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 780-456	EPLAN Data Portal 780-456
↓	↓
	WSCAD Universe 780-456
	↓
	ZUKEN Portal 780-456
	↓

Installation Notes

Commoning



Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

Staggered jumpers are suitable for sophisticated circuit requirements. Push jumpers down until fully inserted!

