



Color: ■ orange

Electrical data

Ratings per IEC/EN	
Rated current	30 A

Physical data

Jumper assignment	1-2-3-4
-------------------	---------

Material data

Note (material data)	Information on material specifications can be found here
Color	orange
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.05 MJ
Weight	5.5 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

PU (SPU)	50 (10) pcs
Packaging type	Box
Country of origin	DE
GTIN	4050821096382
Customs tariff number	85366990990



Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 8.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
282-434/100-000

↓

Documentation				
Bid Text				
282-434/100-000	19.02.2019	xml 2.55 KB	↓	
282-434/100-000	03.03.2017	doc 24.00 KB	↓	

CAD/CAE-Data

CAD data

2D/3D Models
282-434/100-000

↓


CAE data

WSCAD Universe
282-434/100-000


↓

Installation Notes


Commoning




Jumper with safety lid
Jumper in pre-locked position



Jumper with safety lid
Longitudinal switching disconnect terminal blocks with inserted jumper, including safety lid



Jumper with safety lid
Jumper with raised safety lid




Jumper with safety lid
Removing a jumper via safety lid.

Commoning



Jumper with safety lid
Remove jumper via operating tool.



Jumper with safety lid
Remove jumper via operating tool.