

Data Sheet | Item Number: 745-390

Jumper; 10-way; silver-colored

<https://www.wago.com/745-390>



Color: ■ silver-colored

Similar to illustration

Electrical data

Ratings per IEC/EN

Rated current	41 A
---------------	------

Physical data

Pin spacing	10 mm / 0.394 inches
Jumper assignment	1-2-3-4-5-6-7-8-9-10

Mechanical data

Suitable	for 745 Series (6 mm ²) and 2706 Series
----------	-----------------------------------------------------

Material data

Note (material data)	Information on material specifications can be found here
Color	silver-colored
Contact material	Copper alloy
Contact Plating	Tin
Fire load	0 MJ
Weight	10.2 g

Commercial data

Product Group	4 (Printed Circuit Connectors)
PU (SPU)	200 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4017332608442
Customs tariff number	85366990990

Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 745-390			↓

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	↓

CAD/CAE-Data

CAD data			
2D/3D Models 745-390			↓

CAE data			
ZUKEN Portal 745-390			↓

Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.