



Similar to illustration

Rated current	76 A
---------------	------

Jumper assignment	1-2
-------------------	-----

Suitable for 745 Series (16 mm²) and 2716 Series

Weight	3.7 g
--------	-------



Commercial data	
Product Group	4 (Printed Circuit Connectors)
PU (SPU)	400 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4044918303484
Customs tariff number	85366990990

Product Classification	
UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 745-582

↓

Documentation

Additional Information

Technical Section

03.04.2019

pdf

2027.26 KB

↓

CAD/CAE-Data

CAD data

2D/3D Models 745-582


↓

CAE data


ZUKEN Portal 745-582

↓


Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.