



Color: ■ gray

Electrical data

Ratings per IEC/EN

| | |
|---------------|-------|
| Rated current | 125 A |
|---------------|-------|

Physical data

| | |
|-------------------|------------------------|
| Width | 29.1 mm / 1.146 inches |
| Jumper assignment | 1-2 |

Material data

| | |
|------------------------------------|--|
| Note (material data) | Information on material specifications can be found here |
| Color | gray |
| Insulation material (main housing) | Polyamide (PA66) |
| Flammability class per UL94 | V0 |
| Fire load | 0.05 MJ |
| Weight | 15.1 g |

Commercial data

| | |
|-----------------------|---------------|
| PU (SPU) | 100 (25) pcs |
| Packaging type | Box |
| Country of origin | IN |
| GTIN | 4045454074524 |
| Customs tariff number | 85366990990 |

Product Classification

| | |
|-------------|----------------------|
| UNSPSC | 39121410 |
| eCl@ss 10.0 | 27-14-11-40 |
| eCl@ss 9.0 | 27-14-11-40 |
| ETIM 9.0 | EC000489 |
| ETIM 10.0 | EC000489 |
| ECCN | NO US CLASSIFICATION |

Environmental Product Compliance

| | |
|------------------------|-------------------------|
| RoHS Compliance Status | Compliant, No Exemption |
|------------------------|-------------------------|

Downloads

Environmental Product Compliance

| | |
|--|-------------------|
| Compliance Search | |
| Environmental Product Compliance 284-412 | ↓ |

Documentation

| | | | |
|----------|------------|-----------------|-------------------|
| Bid Text | | | |
| 284-412 | 19.02.2019 | xml 2.58 KB | ↓ |
| 284-412 | 19.09.2017 | doc 22.50 KB | ↓ |

CAD/CAE-Data

| | |
|----------------------|-------------------|
| CAD data | |
| 2D/3D Models 284-412 | ↓ |

| | |
|---------------------------|-------------------|
| CAE data | |
| EPLAN Data Portal 284-412 | ↓ |
| WSCAD Universe 284-412 | ↓ |
| ZUKEN Portal 284-412 | ↓ |

Installation Notes

Commoning



Commoning with comb-style jumper bar.
Individual arrangement: 125 A
Two jumpers combined in one clamping unit: 100 A



Connecting 35 mm² (2 AWG) conductors to commoned terminal blocks.
Screw clamp connection, side-entry wiring

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com