

Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585



Features

- Simple and slick integral design with no driver box and without any visible screws

New technology utilization for improved performance

Invisible in-track adaptor for an impressive architectural look

Extremely precise light beams due to the high-quality lens

#80mm die-cast aluminium body, Adjustable beam angle: between 8° - 55° , Textured white finishing colour

Light color temperature: 4000K, natural light

System power: 18W, Fixture lumen output: 1100lm, efficacy: 61lm/W, Ra97 typical, LED chromacity: 2 step MacAdam ellipse LED source (SDCM2), IR/UV free light source without heat radiation

Operating voltage 220-240V / 50-60Hz, DALI suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet.

Compatible with OneTrack

Electrical protection: Class II. Degree of protection: IP20, suitable for indoor environment only

Horizontal rotation: 355°, vertical tilt: 90°

Nominal product dimensions: D.80mmx215mm

5 years warranty. Suitable for track mounting

Product Overview


Product name	CONCORD BEACON MUSE 4000K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Fixture rating	Enclosed
General application	Museums & Galleries, Retail, Hospitality
ETIM Class	EC001744
E-number FI	4170399
Fixture luminous flux (lm)	1100

Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585


Luminaire efficacy (lm/W)	61
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	97
Colour Variation Initial (SDCM)	2
Beam Angle (°)	55
Photobiological Risk Group	RG1
Total power consumption (W)	18
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Product EAN number	5025768625857
Warranty	5 years
Dimming method	DALI
Useful luminous flux (#use)	1100

Photometry




Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585



Technical drawings



Data table

GENERAL DATA

Product name	CONCORD BEACON MUSE 4000K DALI WHITE
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Track mounting
Fixture rating	Enclosed
General application	Museums & Galleries, Retail, Hospitality
Operating temperature range (°C)	-10°C...+35°C
ETIM Class	EC001744
E-number FI	4170399

Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585

Warranty 5 years

OPTICAL DATA

Useful luminous flux (#use)	1100
Fixture luminous flux (lm)	1100
Luminaire efficacy (lm/W)	61
LOR (%)	100
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	97
Colour Variation Initial (SDCM)	2
Luminous Intensity (cd)	1100
Beam Angle (°)	55
Distribution type	Symmetric
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	18
Current (A)	0.084
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Drive current (mA)	500
Inrush Current (A)	16
Inrush Duration (µs)	100
Glow Wire Test (°C)	650

Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585

Energy Efficiency Class (A->G) of contained light source	E
--	---

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

Max. products per 10A C Breaker	50
---------------------------------	----

Max. products per 16A C Breaker	70
---------------------------------	----

Max. products per 16A B Breaker	55
---------------------------------	----

LIFETIME DATA

Lifespan L70 B50	100000
------------------	--------

Lifespan L80 B50	100000
------------------	--------

Lifespan L90 B50	49000
------------------	-------

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
----------------	----------------------------------

IP rating	IP20
-----------	------

IK rating	IK02
-----------	------

Diffuser finish	Frosted
-----------------	---------

Diffuser material	Other
-------------------	-------

Reflector finish	Matt
------------------	------

Nominal Product Length (mm)	215
-----------------------------	-----

Nominal Product Width (mm)	80
----------------------------	----

Nominal Product Height (mm)	270
-----------------------------	-----

Nominal Product Diameter (mm)	80
-------------------------------	----

Weight (kg)	0.94
-------------	------

PACKAGING

Product EAN number	5025768625857
--------------------	---------------

Packaging single length / height (cm)	30.5
---------------------------------------	------

Packaging single width (cm)	13.5
-----------------------------	------

Packaging single depth (cm)	20.5
-----------------------------	------

DUN14 (inner)	05025768625857
---------------	----------------

Units per outer package	1
-------------------------	---

Packaging outer length / height (cm)	30.5
--------------------------------------	------

Packaging outer width (cm)	13.5
----------------------------	------

Concord

CONCORD BEACON MUSE 4000K DALI WHITE 2062585

Packaging outer depth (cm)	20.5
----------------------------	------

SAFETY DATA

Optimal operating condition (°C)	-10-35
----------------------------------	--------

Special purpose lamp	No
----------------------	----

Dry applications use only	Yes
---------------------------	-----

Suitable for household illumination	No
-------------------------------------	----