

# Concord

## OPTIX RECESSED 1200 2L LUMI 4K ALU SSC

2023839



### Features

- OPTIX RECESSED 1200 2L LUMI 4000K ALU SSC is a ceiling recessed luminaire for office and education applications with Aluminised plastic extra low glare optics and RAL9016 colour fixture body. SylSmart Standalone enabled. 4000K Neutral White LED, chromaticity tolerance of 3-step MacAdam ellipse. For 4000K - Colour rendering index Ra >98; Melanopic Ratio MEER: 0.782; Fidelity Index R#: 93; Gamut Index R#: 98. For 4000K luminous flux: 3800lm. Power consumption: 37W. Luminaire efficacy: 103lm/W. UGR<16 Luminance at 65° <200 Cd/m<sup>2</sup>, IK07, IP20. Photobiological safety risk group 0. Electrical protection Class I. Glow wire test 850°C. 60,000hrs L80B20 lifespan.

### Product Overview

<b>Product name</b>	OPTIX RECESSED 1200 2L LUMI 4K ALU SSC
<b>Technology</b>	LED LumiNature
<b>Cap/Base</b>	N/A
<b>Housing</b>	Steel
<b>Mount</b>	Ceiling recessed mounting
<b>Fixture rating</b>	Enclosed
<b>General application</b>	Education, Office
<b>ETIM Class</b>	EC002892
<b>Fixture luminous flux (lm)</b>	3810
<b>Luminaire efficacy (lm/W)</b>	103
<b>Light colour</b>	Neutral White
<b>CRI (Ra)</b>	98
<b>Colour Consistency (SDCM)</b>	3
<b>Colour Variation Initial (SDCM)</b>	3
<b>Glare control</b>	< 16

Concord  
by SYLVANIA


# Concord

## OPTIX RECESSED 1200 2L LUMI 4K ALU SSC

2023839

Photobiological Risk Group	RG0
Total power consumption (W)	37
Electrical protection	Class I
Control gear type	LED driver constant current
Housing colour	RAL9016
IP rating	IP20
IK rating	IK07
Product EAN number	5025768238392
Warranty	5 years
Dimming method	SylSmart SSC
Useful luminous flux (#use)	3810

### Photometry



### Technical drawings

