

Technical data sheet

Lightning current arrester MCF-P, 3-pole

Item number: 5096945



Lightning current arrester, type 1+2+3

- Lightning current discharge capacity of 35 kA (10/350) per pole
- Protection level < 1.5 kV
- Lightning protection equipotential bonding according to VDE 0185-305 (IEC 62305)
- Follow current quenching Ifi 50 kA
- Complies with the requirements for the use in the pre-meter area according to VDE-AR-N 4100

Application: industrial plants and buildings with external lightning protection of the classes I to IV.


* Complete = Plug-in arrester and base



Master data

Item number	5096945
Type	MCF-P-3
Description 1	Lightning current arrester
Description 2	pluggable, 3-pole
Manufacturer	OBO
Dimension	255V
Smallest sales unit	1
Unit of quantity	Piece
Weight	158.846 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	2,6574 kg CO2e / 1 Piece

Dimensions



Length	70 mm
Width	108 mm
Height	90 mm

Technical data sheet

Lightning current arrester MCF-P, 3-pole

Item number: 5096945



Technical data

Response time [L-N]	<100 ns
Blow-out	no
Pole version	3
Structural width in division units (division unit, 17.5 mm)	6
Lightning surge current (10/350 µs)	35 kA
Lightning surge current (10/350 µs) [L-N/PE]	35 kA
Lightning surge current (10/350)	105 kA
Torque	44 Lbs
Torque	5 Nm
Installation location	Interior
Remote signalling	no
Function/defect display	Visual
Suitable for outdoor use	no
Combined voltage protection level [L-PEN]	1.5 kV
Maximum continuous voltage (L- N)	255 V
Maximum continuous voltage AC	255 V
Integrated back-up fuse	no
Short-circuit resistance for max. mains-side overcurrent protection	50 kA eff
Conductor cross-section, flexible (fine-wire), max.	35 mm ²
Conductor cross-section, flexible (fine-wire), max.	2 AWG
Conductor cross-section, flexible (fine-wire), min.	16 AWG
Conductor cross-section, flexible (fine-wire), min.	1.5 mm ²
Conductor cross-section, rigid (single-wire/multiwire), max.	2 AWG
Conductor cross-section, rigid (single-wire/multiwire), max.	35 mm ²
Conductor cross-section, rigid (single-wire/multiwire), min.	16 AWG
Conductor cross-section, rigid (single-wire/multiwire), min.	1.5 mm ²
Humidity, min.	5 %
Humidity, max.	95 %
Max. mains-side overcurrent pro- tection	315 A gL/gG
Maximum back-up fuse	315 A
Maximum discharge current (8/20 µs) [L-N]	50 kA
Minimum distance	0 mm
Installation type	DIN rail 35 mm
Nominal discharge current (8/20 µs)	35 kA
Nominal discharge current (8/20 µs) [L-N]	35 kA
Nominal frequency	50 Hz
Nominal voltage AC (50/60 Hz)	230 V
Network form	TN-C
DC network form	no

Technical data sheet

Lightning current arrester MCF-P, 3-pole

Item number: 5096945



Technical data

IT network form	no
Other network form	no
TN network form	no
TN-C network form	yes
TN-C-S network form	no
TN-S network form	no
TT network form	no
OBO_Nominal load current (input/output terminal)	125 A
Ports	One-Port SPD
Test class, type 1	yes
Protection rating	IP20
Protection level	≤1,5 kV
Protection level [L-N]	≤1,5
Signalling on device	Visual
SPD to EN 61643-11	Type 1+2+3
SPD to IEC 61643-1	Class I+II+III
Permitted temperature range, max.	70 °C
Permitted temperature range, min.	-40 °C
TOV voltage [L-N] – fail safe mode – 120 min.	440 V
TOV voltage [L-N] – withstand mode – 5 s	345 V
Number of conductors (without earth)	3