

Data Sheet | Item Number: 745-683

Jumper; 3-way; silver-colored

<https://www.wago.com/745-683>



Color: ■ silver-colored

Similar to illustration

Electrical data

Ratings per IEC/EN

Rated current	76 A
---------------	------

Physical data

Pin spacing	20 mm / 0.787 inches
-------------	----------------------

Jumper assignment	1-2-3
-------------------	-------

Mechanical data

Suitable	for 745 Series (16 mm ²) and 2716 Series
----------	--

Material data

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	silver-colored
-------	----------------

Contact material	Copper alloy
------------------	--------------

Contact Plating	Tin
-----------------	-----

Fire load	0 MJ
-----------	------

Weight	7 g
--------	-----

Commercial data

Product Group	4 (Printed Circuit Connectors)
PU (SPU)	200 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4044918303545
Customs tariff number	85366990990

Product Classification

UNSPSC	39121421
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-44-04-92
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads

Environmental Product Compliance

Compliance Search			
Environmental Product Compliance 745-683			

Documentation

Additional Information			
Technical Section	03.04.2019	pdf 2027.26 KB	

CAD/CAE-Data

CAD data			
2D/3D Models 745-683			

Installation Notes



Inserting a comb-style jumper bar.



To insert a comb-style jumper bar, push it down using a screwdriver until it hits the backstop – 745 Series.



To remove the jumper bar, lift it up using a screwdriver – 745 Series.