



Color: ■ gray

Similar to illustration

Electrical data

Ratings per	IEC/EN 60664-1		
Overvoltage category	III	III	II
Pollution degree	3	2	2
Nominal voltage	-	320 V	-
Rated impulse withstand voltage	-	4 kV	-
Rated current	-	16 A	-

Connection data

Connection 1

Pole number	3
-------------	---

Physical data

Pin spacing	5/5.08 mm / 0.197/0.2 inches
Width	15.3 mm / 0.602 inches
Depth	6.15 mm / 0.242 inches
Jumper assignment	1-2-3

Mechanical data

Suitable for male and female connectors with CAGE CLAMP® connection

Material data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.008 MJ
Weight	0.7 g

Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454565848
Customs tariff number	85366990990

Product Classification

UNSPSC	39121410
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 9.0	EC000489
ETIM 10.0	EC000489
ECCN	NO US CLASSIFICATION

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Approvals / Certificates

General approvals



Approval	Standard	Certificate Name
CSA DEKRA Certification B.V.	C22.2	1466354

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 231-903



Documentation

Additional Information

Technical Section

03.04.2019


pdf

2027.26 KB



Installation Notes

Installation



Notice: Insert jumper bar according to direction of symbols.

□ symbol correlates to the direction of the operating slot.

Notice: Insert jumper bar according to direction of symbols.

○ symbol shows direction to conductor entry.

Coding



Custom comb-style jumper bars are created by breaking off jumper contacts (3 contacts and more).

Installation




Notice: Comb-style jumper bars reduce the conductor cross-section to 1.5 mm² "s" + "f-st."

Commoning



Inserting a comb-style jumper bar via multipole operating tool – with the female or male connector being supported in a suitable holding device.

Installation



Operating tool for comb-style jumper bars (231-902)

Application



Both male and female connectors can be pre-assembled with comb-style jumper bars upon request.