







Een volledig, veelzijdig systeem van modulaire containers, perfect geïntegreerd in de SYSTEM huishoudelijke serie en voldoet aan de installatiebehoeften met hoge bescherming van huishoudelijke, commerciële en industriële sectoren. De 27 COMBI serie is beschikbaar in de versie IP40 en in waterdichte versies met beschermingsgraad IP55, IP65 en IP66, aanbevolen voor alle buitentoepassingen onderhevig aan extreme atmosferische omstandigheden.

Omschrijving	8 modules	Aant. modules	8
Kleur	Antraciet RAL 7021	Aant. uitbrekopeningen Ø23	2 aan bodem
Soort uitbrekopeningen	Verwijderbaar met gereedschap	IP waarde	IP40
Isolatie klasse	II	Mechanische weerstand	IK07
Compartment voorbereiding	2	Kenmerken	Halogeenvrij
Dekselschroeven	Corrosiebestendig staal	Koppel schroeven aandraaien	0.8 NM
Buitenste afm. LxHxD (mm)	132x132x54	Gloeidraadtest	650 °C
Thermodruk met kogel	70 °C	Standaard	EN 50085-2-1
Installatie temperatuur	-5 +60 °C	Electrocod	0212

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Not resistant	Limited resistance	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY



IP

IP40



II

IK


IK07




Halogeenvrij

GWT

650 °C



70 °C



-5 +60 °C

STANDARDS/APPROVALS

