

Product Specifications

Product Family : Zybrnet
Category : Cat 5e
Product : Zybrnet Cat5e Plug – Standard UTP
Item no. : 010.04.0438


Approvals

RoHS UL 94V-0 / 94V-2

Applications & Features

✓ Ideal for OEM patch cable production

Product drawing



BLADE:	E	EB	Y	YB	Z	A	AE	AB	EC	AL	ZL	YBL
Drawing												
Mark					✓							
GOLD PLATING	3Mu"	3u"	6u"	15u"	30u"	50u"	CABLE TYPE	ROUND	FLAT			
Mark						✓	Mark		✓			

Physical properties

Materials

Housing	Polycarbonate (PC), UL94V-0
Contact Blade	Copper Alloy
Insert/Divider	-
Contact Plating	50 micro inches gold

Electrical & mechanical properties

Electrical

Di-electric withstanding voltage	1000V AC @ 60Hz, 1 min
Insulation resistance	100M ohms (min.)
Contact Resistance	20m ohms (max.)
DC Resistance	0.1 ohm (max.)
Current Rating	2.0 A

Mechanical

Compatible AWG	AWG 24 to 26
Insertion Cycles	200 cycles (min.)
Operation Temperature	-10°C ~ +60°C
Compatible Wire OD	0.96mm to 1.02mm
Plug Tensile Strength	9.1 kg
Cable Type	Solid & stranded

