

Isoline  
ISOLINE 1690MM 4K ASYR 5C  
0042528




PRODUCT OVERVIEW

|                                 |                                  |
|---------------------------------|----------------------------------|
| Product name                    | ISOLINE 1690MM 4K ASYR 5C        |
| Technology                      | LED                              |
| Cap/Base                        | N/A                              |
| Housing                         | Aluminium                        |
| Mount                           | Suspended                        |
| Fixture rating                  | Enclosed                         |
| Warranty                        | 5 years                          |
| Fixture luminous flux (lm)      | 8000                             |
| Luminaire efficacy (lm/W)       | 140                              |
| Colour temperature (K)          | 4000                             |
| Colour Code                     | 840                              |
| CRI (Ra)                        | 80                               |
| Colour Variation Initial (SDCM) | SDCM3                            |
| Photobiological Risk Group      | RG1                              |
| Total power consumption (W)     | 57                               |
| Electrical protection           | Class I                          |
| Control gear type               | LED driver constant current      |
| LED Flickering Rate             | Ultra low (5% or less)           |
| Housing colour                  | RAL 9016 - Traffic white / Bezel |
| IP rating                       | IP20                             |
| IK rating                       | IK03                             |
| Product EAN number              | 5410288425283                    |

PHOTOMETRY

Isoline  
*ISOLINE 1690MM 4K ASYR 5C*  
0042528



**TECHNICAL DRAWINGS**

