

PLP-P-PK: Galvanised bracket for backplate elbow



Commercial information

Wall mounted bracket

This 3 mm full steel galvanized bracket can be used for different applications: shower & bath faucets, under sink mounting and robust anchoring behind plaster wall frame[1]work. It has the following specifications:

- Robust steel bracket
- Rigid wall attachment
- Accurate interaxis fixation
- Various depths for concealed mouting
- Free choice of any backplate fitting

Basic unit dimensions

Height	35 mm
Length	210 mm
Width	35 mm
Net weight	0.220 kg

Certificates

Applications

Potable water, Heating, Compressed air, Gas, Sanitary

Solutions

Building installations, Industry, Oil & gas, Utility

Technical characteristics

Inlay	None	Outer pipe diameter	16 32 Millimetre
Connection facility	Other		
Connection size, connection facility	Other		
Flexible connection facility	✘		
Lock facility	Other		
FM quality mark	✘		
UL quality mark	✘		
ULC quality mark	✘		
LPCB quality mark	✘		
Suitable for steel tube	✓		
Suitable for thin-walled pipe	✓		
Suitable for stainless steel tube	✓		
Suitable for copper tube	✓		
Suitable for aluminium tube	✓		
Suitable for cast iron pipe	✓		
Suitable for plastic tube	✓		
Suitable for pipe coil	✓		
KIWA certified	✘		