





Waterdichte inbouwkasten voor noodgevallen en speciale toepassingen met DIN-rail. Verkrijgbaar in de kleuren rood RAL 3000 of grijs RAL 7035. Dankzij de noodhamer, verkrijgbaar als accessoire, verzegelbaar masker en halogeenvrije materialen zijn de kasten ideaal geschikt voor toepassingen in openbare ruimtes.

Nominale stroom (A)	125	Isolatie klasse	II
Kleur	Rood RAL 3000	Buitenste afm. LxHxD (mm)	145 x 200 x 70
IP waarde	IP55	Installatie	Inbouwkasten
Materiaal	Technopolymeer	Mechanische weerstand	IK08
Nominale spanning (V)	400	Gloeidraadtest	650 °C
Bedrijfstemperatuur	-15 ÷ +60 °C	Type materiaal	Halogeenvrij conform EN 60754-2
Electrocod	0321	Thermodruk met kogel	70 °C
Standaard	EN 60670-1 (CEI 23-48) IEC60670-24 CEI 23-49	Isolatie spanning	750 V
Vermogens verlies (W)	12	Aant. modules EN 50022	4

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Ethyl alcohol		
Resistant	Not resistant	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance

DIMENSIONAL



TECHNICAL SYMBOLOGY



II

IP


IP55

IK

IK08

GWT

650 °C



-15 ÷ +60 °C



Halogeenvrij conform EN 60754-2



70 °C

STANDARDS/APPROVALS

