

Component terminal block; double-deck; with varistor; for DIN-rail 35 x 15 and 35 x 7.5 and 35 x 15 and 35 x

7.5; 2.5 mm²; CAGE CLAMP[®]; 2,50 mm²; gray


https://www.wago.com/280-502/281-610







Similar to illustration



Short description:

WAGO's component terminal block with single-stage surge suppression device and direct connection to DIN-35 rail is equipped with a varistor.

Features:

- Protect your system against overvoltage
- Slim, space-saving design
- Control operational costs by preventing expensive, unplanned downtime
- High operational reliability and system uptime

Electrical data	
Nominal operating voltage	48 VDC
Maximum continuous voltage	65 VDC
Rated continuous current	20 A
Nominal discharge current (8/20 µs) (line)	300 A
Discharge current (max.)	1.2 kA
Protection level (8/20 µs)	≤ 135 VDC
Capacitance	≤ 500 pF

https://www.wago.com/280-502/281-610



Safety and protection

Protection type IP00

Connection data

Wiring direction Front-entry wiring

Connections (number) 2

Connection technology CAGE CLAMP®

Solid conductor $0.08 \dots 2.5 \text{ mm}^2 / 28 \dots 14 \text{ AWG}$ Fine-stranded conductor $0.08 \dots 2.5 \text{ mm}^2 / 28 \dots 14 \text{ AWG}$

Strip length 8 ... 9 mm / 0.31 ... 0.35 inches

Physical data

 Width
 5 mm / 0.197 inches

 Height
 64 mm / 2.52 inches

 Depth from upper-edge of DIN-rail
 58.5 mm / 2.303 inches

Mechanical data

Design with direct connection to DIN-rail

Mounting type DIN-35 rail

Material data

Color gray

Insulation material (main housing) Polyamide (PA66)

Material group

Flammability class per UL94 V0

Fire load 0.246 MJ

Weight 8.5 g

Environmental requirements

Ambient temperature (operation) -25 ... +70 °C

Processing temperature -35 ... +85 °C

Operating altitude (max.) 2000 m

27-14-11-27

Standards and specifications

Standards/specifications EN 60947-7-1 EN 60512-5-2

EN 00312

Commercial data

eCl@ss 10.0

Product Group 1 (Rail Mounted Terminal Blocks)

eCl@ss 9.0 27-14-11-27
ETIM 9.0 EC000903
ETIM 8.0 EC000903

PU (SPU) 50 pcs
Packaging type Box

Country of origin DE

GTIN 4050821861171

Customs tariff number 85369010000

https://www.wago.com/280-502/281-610



Environmental Product Compliance

RoHS Compliance Status Compliant,No Exemption

Approvals / Certificates

Declarations of conformity and manufacturer's declarations

Approval Standard Certificate Name

EU-Declaration of Conformity

WAGO GmbH & Co. KG

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance

280-502/281-610

Documentation

Bid Text			
280-502/281-610	19.02.2019	xml 3.35 KB	$\underline{\downarrow}$
280-502/281-610	11.02.2015	doc 25.50 KB	$\underline{\downarrow}$

CAD/CAE-Data

CAD data

2D/3D Models 280-502/281-610 CAE data

EPLAN Data Portal 280-502/281-610

WSCAD Universe 280-502/281-610

ZUKEN Portal 280-502/281-610 \downarrow

https://www.wago.com/280-502/281-610



1 Compatible Products

1.1 Required Accessories

1.1.1 End plate

1.1.1.1 End plate

Item No.: 280-340



Item No.: 280-341

End and intermediate plate; 2.5 mm thick; gray

In : 000 041

End and intermediate plate; 2.5 mm thick; orange

1.2 Optional Accessories

1.2.1 Insulation stop

1.2.1.1 Insulation stop



Insulation stop; 0.08 - 0.2 mm² "s" (0.14 mm² "f-st"); 5 pieces/strip; white

60000

Item No.: 280-471

Insulation stop; 0.25 - 0.5 mm²; 5 pieces/ strip; light gray 460m

Item No.: 280-472 Insulation stop; 0.75 - 1 mm²; 5 pieces/ strip; black

1.2.2 Jumper

1.2.2.1 Jumper

Item No.: 280-470

Item No.: 280-490
Jumper; 10-way; insulated; gray

Item No.: 280-482

Jumper; 2-way; insulated; gray

Item No.: 280-492

Jumper; 2-way; insulated; gray

Item No.: 280-483

Jumper; 3-way; insulated; gray



<u>Item No.: 280-484</u>

Jumper; 4-way; insulated; gray

Item No.: 280-485

Jumper; 5-way; insulated; gray

1.2.3 Marking

1.2.3.1 Marker



Item No.: 793-502

WMB marking card; as card; MARKED; 1 ... 10 (10x); not stretchable; Horizontal marking; snap-on type; white

Item No.: 793-503

WMB marking card; as card; MARKED; 11 ... 20 (10x); not stretchable; Horizontal marking; snap-on type; white Item No.: 793-504

WMB marking card; as card; MARKED; 21 ... 30 (10x); not stretchable; Horizontal marking; snap-on type; white

4

Item No.: 793-505

WMB marking card; as card; MARKED; 31 ... 40 (10x); not stretchable; Horizontal marking; snap-on type; white



Item No.: 793-506

WMB marking card; as card; MARKED; 41 ... 50 (10x); not stretchable; Horizontal marking; snap-on type; white Item No.: 793-501

WMB marking card; as card; not stretchable; plain; snap-on type; white Item No.: 2009-115

WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white

https://www.wago.com/280-502/281-610



1.2.4 Tool

1.2.4.1 Operating tool



Item No.: 210-720
Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; multicoloured

Subject to changes. Please also observe the further product documentation!